

Survey of the Subdivisions of T. 35 N., R. 22 E.

Chains.


N. $0^{\circ} 02'$ W. on true line bet. secs. 3 and 4.

Over broken land. Asc. steep S. slope.

11.50 Top of spur, 250 ft. above sec. cor. projects SW. Desc.

NW. slope, bearing down over broken land.

17.00 Small stream, course SW., 30 ft. below spur, from spring NE., 30 lks. dist. Asc. abrupt S. slope.

33.50 Rimrock, 570 ft. above stream, bears W. and S. 80° E., turning S. at intersection with spur. Asc. more gradual.40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. This cor. is 60 ft. above rimrock.; from which

A juniper, 8 ins. dia., bears N. 50° E., 53 lks. dist., marked $\frac{1}{4}$ S 3 BT.

45.44 Intersect the 7th St. Par. N. at a point 4.51 chs., S. $89^{\circ} 45'$ W. of the S.C. of secs. 34 and 35, at which point set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in the ground, for C.C. of secs. 3 and 4, with brass cap mkd.

T36N R22E
S34

S4 S3

T35N R22E

C C

1917

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of cor. This cor. is 60 ft. above rimrock.; from which

A juniper, 12 ins. dia., S. $60\frac{1}{2}^{\circ}$ W., 190 lks. dist.,

marked T 35 N R 22 E S 4 C C BT.

Land, steep mountainous slopes, general drainage S.

Soil, heavy rocky clay loam, shallow, with many outcrops and exposed ledges.

Scant growth of sage and bunch grass.

Scattering juniper.