	Survey of the Subdivisions of T. 35 N., R. 22 E.	
Chains 9.10	Small rocky spur, 90 ft. above sec. cor. projects W.	
	Desc. very gradual NE. slope 90 ft. to	
40.00	Set an iron post, 3 ft. long, 1 in dia., 20 ins. in the ground to solid rock, with mound of stone around, for $\frac{1}{4}$	
31,0 E	sec. cor., with brass cap mkd.	
1027 5.10	side , we see the factor fills of factor sides of factors	
	1917	
	and raisea mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of	
9	cor.	
45.39		
17.	89° 54' W. off the S.C. of secs. 33 and 34, at which	
	of, to Rimmook, 15 at. Bank, 890 for above cubyon, bear	
	point set an iron post, 3 ft. long, 2 ins. dia., 20 ins.	
	in the ground, for C.C. of secs. 4 and 5, with brass cap	
-	the ground, alw ears of every this this cold the	

T36N S3	
S5	S4
T35N	R22E
C	C

and raise a mound of stone, 2 ft. base, $l\frac{1}{2}$ ft. high, S. of cor.

Land, rolling mountainous, draining SE.

Soil, heavy clay loam, slightly rocky, 20 ins. deep, with solid rock subsoil.

Good growth of sage, deer browse and bunch grass. Scattering juniper.

From the cor. of secs. 5, 6, 31 and 32 on the S. bdy., which is a burnt granite stone, 8 X 8 X 4 ins., above ground, firmly set, marked with 5 notches on E. and 1 notch on W. edges; mound of stone W.

N. 0° 04' W. on true line bet. secs. 31 and 32.

Over broken land. Desc. NW. slope.

9.30 Canyon, 30 ft. below sec. cor., course S. 60° W. Asc. SW. slope.