

Retracement of the South Boundary of T. 35 N., R. 24 E.

Chains From the cor. of Ts. 34 and 35 N., Rs. 23 and 24 E., which is an iron post, 3 ft. long, 3 ins. dia., showing 12 ins. above ground, marked and witnessed as described by the Surveyor General.

East on retracement of the S. bdy. of T. 35 N., R. 24 E. on the S. bdy. of sec. 31.

37.51 Find no evidence of the old $\frac{1}{4}$ sec. cor.

Continue East on retracement on the S. bdy. of T. 35 N., R. 24 E., searching for old cors. and setting temp. points at 40.00 and 80.00 chs.

477.51 As no cors. have been found on this line, set temp. cor. of Ts. 34 and 35 N., Rs. 24 and 25 E..

Independent Resurvey of portion of the S. Bdy. of T. 35 N., R. 24 E.

As there are no old cors. on this line and secs. 31 and 32 have been previously surveyed; proceed to the temp. cor. of secs. 4, 5, 32 and 33, which is a point 157.51 chs. E. of the Ep. cor. above described and set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in the ground, with brass cap mkd.

T35N	R24E
S32	S33
S5	S4
T34N	R24E
1917	

dig pits, 18 X 18 X 12 ins., in each sec., 5 $\frac{1}{2}$ ft. dist.

As there are no subdivisions dependent on the remainder of this line and to conform with the Special Instructions governing this survey, begin at the above described cor. and make an independent resurvey as follows:

- East on true line on the S. bdy. of sec. 33.
- Over nearly level land.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.