

Dependent Resurvey of the Subdivisions of T. 35 N., R. 24 E.

Chains.

S. 89° 47' W. on true line bet. secs. 30 and 31.
Over nearly level land.


20.08 A point 67 lks. N. of the NW. cor. of a fence, bearing S. and N. 85° E.

A point 13 lks. S. of the SE. cor. of a fence bearing N. and W.

Road, bears N. 15° E. and W.

21.10 Wash, 20 lks. wide, course S. 5° E.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.



dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.

45.50 Wards house bears S. 81 lks. dist.

68.50 Hualipi P.O. bears S. 133 lks. dist.

77.40 Intersect the cor. of secs. 25, 30, 31 and 36, which is an iron post, 3 ft. long, 3 ins. dia., showing 12 ins. above ground, marked and witnessed as described by the Surveyor General.

Land is gently rolling valley land, draining to the S. Soil is a light brown clay loam, slightly alkaline, 10 ins. deep, with clay subsoil.

There is a good growth of greasewood, shadscale and rye grass. No timber.

Survey of the Subdivisions of T. 35 N., R. 24 E.

From the cor. of secs. 1, 2, 35 and 36 on the S. bdy. N. 0° 01' W. on true line bet. secs. 35 and 36.
Over nearly level land.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for 1/4 sec. cor., of secs. 35 and 36, with brass cap mkd.

