


Survey of the Subdivisions of T. 35 N., R. 24 E.

Chains



raise a mound of stone, 4 ft. base, 1½ ft. high, around post. This ¼ sec. cor. is 28 ft. below spur. Desc. NE. slope.


49.90 Ravine, 10 lks. wide, 92 ft. below ¼ sec. cor., course SE. Asc. S. slope.

63.50 Top of spur, 206 ft. above ravine, projects SE. Desc. NW. slope.

67.50 Ravine, 12 lks. wide, 69 ft. below spur, course SE. Asc. S. slope.

108.21 Intersect the 7th St. Par. N. at a point 8.91 chs., S. 89° 55' W. of the S. C. for secs. 35 and 36, at which point I set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in the ground, for C.C. of secs. 1 and 2, with brass cap mkd.

T36N R24E  
S35



raise a mound of stone, 2 ft. base, 1½ ft. high, S. of cor. Cor. is 459 ft. above ravine.

Land is rocky, broken mountainous, draining to the SE.

Soil, heavy clay loam, mixed with shale rock, very shallow on spurs and ridges, with solid rock subsoil.

Scant growth of greasewood and shadscale.

No timber.

From the cor. of secs. 2, 3, 34 and 35 on the S. bdy. N. 0° 02' W. on true line bet. secs. 34 and 35.

Over nearly level land. Asc. gentle S. slope.

17.00 Top of low ridge, 22 ft above sec. cor., bears W. and S. 15° W. Desc. gentle NE. slope.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the