

Survey of the Subdivisions of T. 35 N., R. 24 E.

Chains

$\frac{1}{4}$

S5 S4

1917

raise a mound of stone, 2, ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

69.50 Wash, course S. 45° W.

70.50 Wash, course S. 70° W.

73.00 Wash, course S. 45° W.

107.87 Intersect the 7th St. Par. N. at a point, 8.81 chs. S. 89° 55' W. of the S.C. of secs. 32 and 33, at which point set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in the ground, for C.C. of secs. 4 and 5, with brass cap mkd.

T36N R24E

S32

S5 S4

T35N R24E

C C

1917

raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of cor.

Land, gently sloping and uneven valley, draining SW.

Soil, gravelly compact clay, 3 ft. deep, mixed with wasted rocks, with fine coating of sand.

Undergrowth, greasewood and shadscale.

No timber.

From the re-established cor. of secs. 29, 30, 31 and 32, heretofore described.

North on true line bet. secs. 29 and 30.

Over nearly level land. Medium undergrowth.

9.70 Road, Blackrock to Hualipi, bears E. and W.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$

S30 S29

1917