

East Boundary of T.43 N.,R.25 E.

Chains.
 21.30 Top of rim rock ledge, 30 ft. high, facing SE., 50 ft. above bottom of canyon, bears N.30°E. and S.30°W.; descend gradually rolling NW. slope. 30 ft. to the 1/4 sec. cor.

40.00 Set an iron post 3 ft. long, 1 in. diam., 26 ins. in the ground for 1/4 sec. cor., with brass cap marked

1/4 S31
1917

raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor. Ascend gradually over rolling land, 60 ft. to the Tp. cor.

79.60 Intersect E. bdy. of T.43 N., R.24 1/2 E., North, 12.67 chs. dist. from the cor. of Ts. 42 and 43 N., R.24 1/2 E., described in Book on T.43 N., R.24 1/2 E. At point of intersection, set an iron post 3 ft. long, 3 ins. diam., 24 ins. in the ground for cor. of Ts. 42 and 43 N., R.25 E., with brass cap mkd.

T43N
R25E
S31
S6
T42N

1918

raise a mound of stone, 2 ft. base, 1 1/2 ft. high, E. of cor. Land, rolling hills, drainage to the NE.

Soil, stony heavy clay and adobe, exposed rim rock ledges of volcanic formation along canyons.

Undergrowth, scanty sage brush.

East Boundary of T.43 N.,R.25 E.

From the cor. of Tps. 42 and 43 N., R.25 E. on the W. bdy. of T.42 N., R.26 E., hereinbefore described.

N.1°13'W., on a true line on the E. bdy. of sec. 36.

Over high rolling land, descend gradual slope 100 ft. to the 1/4 sec. cor.

1.13 The cor. of Tps. 42 and 43 N., R.26 E., heretofore described. Change bearing of line to North, and continue survey bet. secs. 31 and 36.

31.00 A small spring on line.

40.00 Set an iron post 3 ft. long, 1 in. diam., 26 ins. in the ground for 1/4 sec. cor., with brass cap marked