

Chains

No timber.

51

From the cor. of secs. 9 and 16.

N. 0° 17' E. on a true line along the E. bdy. of sec. 9.

Over rolling land sloping W. ascend.

23.70 A point which has a northing of 40.00 chs. from the cor. of secs. 10 and 15.

Set an iron post 3 ft. long, 1 in. diam., 26 ins. in the ground for the 1/4 cor. of sec. 10, with brass cap mkd.

1/4

S10

1917

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, E. of cor.

34.90 Top of spur, 20 ft. above 1/4 sec. cor., projects W.; descend N. slope 50 ft. to the 1/4 cor. of sec. 9.

41.35 A point by proportionate measurement for the reestablished 1/4 cor. of sec. 9.

Set an iron post 3 ft. long, 1 in. diam., 26 ins. in the ground for the 1/4 cor. of sec. 9, with brass cap mkd.

1/4

S9

1917

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

Descend gradual slope over gently rolling bench land sloping to the NW.

61.05 Intersect Camp McGarry Military Reservation boundary at a point 184.67 chs. N. 72° 21' W. of cor. No. 2, heretofore described. At the point of intersection I build a cor. as follows:

Set an iron post 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of fractional secs. 9 and 10, with brass cap mkd.