

Chains

40.00 set temp.  $\frac{1}{4}$  sec. cor. No traces of the old  $\frac{1}{4}$  cor. of secs. 1 and 6 found after diligent search.

84.31 Intersect a point on E. and W. line, 91 lks. W. of the old cor. of Tps. 43 and 44 N., Rs. 26 and 27 E., hereinafter described. This mile bears N.  $0^{\circ} 37'$  E. and its length is 84.32 chs.

Dependent Resurvey of Portion of West Boundary T. 43 N., R. 27 E.

As there are subdivisions dependent upon the south  $\frac{1}{2}$  mile and the north 2 miles of the west boundary of T. 43 N., R. 27 E. I make a dependent <sup>re</sup> survey of this portion of the boundary and an independent <sup>re</sup> survey of the remaining portion.

3/24  
The old cor. of Tps. 43 and 44 N., Rs. 26 and 27 E. is a basalt stone, 12 X 15 X 18 ins., firmly set in a mound of stone, marked with 6 grooves on the N. and E. edges. I chisel additional markings of 6 grooves on the S. side of this cor.; and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, E. of the cor., thus making it a cor. only of Tps. 43 and 44 N., R. 27 E., hereafter.

Thence, S.  $0^{\circ} 37'$  W. on a true line on the W. bdy. of sec. 6 Over very rocky and uneven land sloping W.; descend.

4.30 Bottom of depression, 50 ft. below Tp. cor., drains E.; ascend.

15.30 Top of rocky spur, 40 ft. above bottom of depression, projects E.; descend.

30.30 Dry wash from canyon, 2.00 chs. wide, course N.  $80^{\circ}$  E., 100 ft. below top of spur; ascend gradually.

32.60 Ascend NE. slope, 120 ft. to the  $\frac{1}{4}$  sec. cor.

42.16 A point by proportionate measurement for the reestablished  $\frac{1}{4}$  cor. of sec. 6.

Set an iron post 3 ft. long, 1 in. diam., 26 ins. in the ground for the  $\frac{1}{4}$  cor. of sec. 6; with brass cap mkd.