

Chains

the  $\frac{1}{2}$  sec. cor. of sec. 31, bears N..E. and SW.; ascend over rounding ridge, bearing N. and S., 60 ft. to the Tp. cor.

66.34 The old cor. of Tps. 42 and 43 N., Rs. 26 and 27 E., which is a basalt stone, 10 X 12 X 16 ins., firmly set in a mound of stone, marked with 6 notches on the N., S., E. and W. edges. I remonument the cor. for the SW. cor. of T. 43 N., R. 27 E. as follows:

Set an iron post 3 ft. long, 3 ins. diam., 20 ins. in the ground to solid rock and in a mound of stone, for the SW. cor. of T. 43 N., R. 27 E., with brass cap mkd.

T43N

R27E

S31

S1

T42N

R26E

1917

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, E. of cor.

I now change the bearing of my line to South.

Ascend gradually along E. slope of ridge.

73.06 The SE. cor. of Tp. 43 N., R. 26 E., heretofore described.

Land, mountainous, 56.10 chs. N. and NW. exposure,

remainder of mile has a NE. exposure.

Soil, heavy and rocky clay loam, many exposed ledges of rock.

Undergrowth, sagebrush, bunch grass.

No timber.

---

Survey of North Boundary of T. 43 N., R. 26 E.

---

From the cor. of Tps. 43 and 44 N., Rs. 25 and 26 E., hereafter described.

East on a true line bet. secs. 6 and 31.

Over high mesa land descend gradually.

12.90 Rim rock ledge of rock, 20 ft. high, facing E., bears