

Dependent Resurvey. Fractional Subdivisions T. 46 N., R. 28 E.

Chains

Set an iron post 3 ft. long, 2 ins. diam., 24 ins. in the ground alongside the old cor. for the cor. of secs. 4 and 9, with brass cap mkd.

T46N
S4
S9
R28E

1917

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

I now change the bearing of my line to N. $2^{\circ} 33'$ E.

40.04 Set an iron post 3 ft. long, 1 in. diam., 18 ins. in the ground to solid rock and in a mound of stone, for the $\frac{1}{4}$ cor. of sec. 3, with brass cap mkd.

 $\frac{1}{4}$

S3

1917

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor.

47.56 Dry wash, 30 lks. wide, course SW.

47.82 A point by proportionate measurement for the reestablished cor. of sec. 4.

Set an iron post 3 ft. long, 1 in. diam., 14 ins. in the ground to solid rock and in a mound of stone, for the $\frac{1}{4}$ cor. of sec. 4, with brass cap mkd.

 $\frac{1}{4}$

S4

1917

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

90.65 The old cor. of secs. 3, 4, 33 and 34 on the N. bdy. of the Tp., which is a volcanic stone, 9 X 6 X 8 ins., set in a mound of stone, mkd. with 3 grooves on the E. and W. edges. I remonument the cor. for two secs. as follows:

Set an iron post 3 ft. long, 2 ins. diam., 24 ins. in the ground alongside the old cor. for the cor. of secs. 3