

Subdivisions of T. 46 N., R. 28 E.

Chains

and 4, with brass cap mkd.

S4	S3
T46NR28E	

1917

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, S. of cor.

Land, rolling hills, general drainage to the W.

Soil, sandy and rocky clay loam, shallow in many places, rocky subsoil.

Undergrowth, sagebrush, greasewood, bunch grass.

No timber.

Subdivisions of T. 46 N., R. 28 E.

From the standard cor. of secs. 35 and 36 on the S. bdy. of the Tp., heretofore described.

North on a blank line bet. secs. 35 and 36.

40.00 Set temp. 1/4 sec. cor.

81.31 Anpoint which is due east of the cor. of secs. 26, 27, 34 and 35, as determined by operations hereinafter recorded.

Set an iron post 3 ft. long, 2 ins. diam., 24 ins. in the ground, for the cor. of secs. 25, 26, 35 and 36, with brass cap mkd.

T46N	
S26	S25
S35	S36
R28E	

1917

Land, overflowed and very wet, pits impracticable.

Thence,

South on a true line bet. secs. 35 and 36.

Over overflowed alkali flat and lake bed.

40.00 Set an iron post 3 ft. long, 1 in. diam., 26 ins. in the ground for 1/4 cor. of sec. 36, with brass cap mkd.

1/4

S36

1917