

SUBDIVISION OF T.18 N., R.68 E.

Chains

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy .
of Tp.; thence

N.0° 01'W., bet. secs. 35 and 36.

Ascend along SW. slope over mountainous land, through
scattering sagebrush and grass undergrowth, and dense
mahogany and scattering cedar and pinon timber.

32.20 Spur, 470 ft. above sec. cor., projects S.70°W.

Descend along NW. slope.

40.00 180 ft. below spur.

Set an iron post, 3 ft. long, 1 in. dia., 24 ins. in the
ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

$$\begin{array}{c} \frac{1}{4} \\ \hline \text{S35} \mid \text{S36} \\ \hline 1917 \end{array}$$

From which

A mahogany, 9 ins. dia., brs. S.38°E., 31 lks.
dist., marked $\frac{1}{4}$ S 36 B T.

A spruce, 10 ins. dia., brs. S.55°W., 19 lks.
dist., marked $\frac{1}{4}$ S 35 B T.

69.20 Gulch, 735 ft. below $\frac{1}{4}$ sec. cor., course W.

From this point a spring of clear water, brs. W. about
10.00 chs. dist.

Ascend .

80.00 75 ft. above gulch.

Set an iron post, 3 ft. long, 2 ins. dia., 20 ins. in the
ground, to solid rock, and 4 ins. in a mound of stone,
for the cor. of secs. 25, 26, 35 and 36, marked on
brass cap

$$\begin{array}{c} \text{T18N} \mid \text{R68E} \\ \text{S26} \mid \text{S25} \\ \hline \text{S35} \mid \text{S36} \\ \hline 1917 \end{array}$$

From which

A pinon, 12 ins. dia., brs. N.18 $\frac{1}{2}$ °E., 28 lks.
dist., marked T 18 N R 68 E S 25 B T.

A pinon, 14 ins. dia., brs. S.41 $\frac{3}{4}$ °E., 105 lks.
dist., marked T 18 N R 68 E S 36 B T.

A pinon, 12 ins. dia., brs. S.74°W., 66 lks. dist.,