

14.

East Boundary of T. 9 N., R. 30 E.

Chs.

N. bet. secs. 1 and 6.

Over rolling and rough mountainous land, through dense short shadscale; desc.

2.50 Bottom of draw, 20 ft. below sec. cor., course SW.; asc. abruptly.

8.60 Top of spur, 145 ft. above bottom of draw, projects W. 12 chs.; desc. abruptly.

12.10 Bottom of draw, 85 ft. below top of spur, course W.; asc. abruptly.

19.70 Top of spur, 175 ft. above bottom of draw, projects W. 30 chs.; asc. across head of draw, course W.

23.40 Top of spur, 20 ft. above head of draw, projects NW. 30 chs.; desc.

31.60 Dry wash, 200 lks. wide 12 ft. deep, in the bottom of draw, 100 ft. below top of spur, course W.; asc.

36.50 Top of spur, 60 ft. above bottom of draw, projects W. 15 chs.; desc. N. slope.

40.00 Set an iron post 3 ft. long, 1 in. diam., 12 ins. in the ground to solid rock and in a mound of stone for $\frac{1}{4}$ sec. cor., with brass cap marked:
$$\begin{array}{c} \frac{1}{4} \\ | \\ S\ 1 \quad S\ 6 \\ | \\ 1917 \end{array}$$
and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. This cor. is 40 ft. below top of spur.41.70 Dry wash, 30 lks. wide 8 ft. deep, in the bottom of draw, 30 ft. below $\frac{1}{4}$ sec. cor., course W.; asc.

68.80 Top of ridge, 130 ft. above bottom of draw, bears N.80°E. and S.80°W. 20 chs.; desc.

73.90 Bottom of draw, 80 ft. below top of ridge, course S.80°W.; asc.

77.50 Top of spur, 45 ft. above bottom of draw, projects S.80°W. 20 chs.; desc.

80.00 Set an iron post 3 ft. long, 3 ins. diam., 24 ins. in the