

Chs.

a subsoil of coarse, gravelly, light sand.
 No timber. Very little grass.
 Undergrowth; scattering grease wood and shadscale.
 Drainage W.


to here

Subdivision of T. 9 N., R. 30 E.

From the cor. of secs. 1, 2, 35 and 36, on the N. bdy.
 of the Tp., heretofore described,
 S.0°01'E. bet. secs. 1 and 2.

Over rolling mountainous land, through scattering short
 shadscale and grease wood; desc. S. slope.

- 8.80 Dry wash, 50 lks. wide 4 ft. deep, in the bottom of draw,
 80 ft. below sec. cor., course SW.; asc.
- 12.80 Top of spur, 50 ft. above wash, projects S.80°W.; desc.
- 16.80 Dry wash, 50 lks. wide 6 ft. deep, 35 ft. below top of
 spur, course S.80°W.; desc. gradually over rolling land.
- 21.30 Dry wash, 6 chs. wide 10 ft. deep, course S.80°W.
- 38.60 Dry wash, 100 lks. wide 5 ft. deep, in the bottom of hol-
 low, 25 ft. below wash noted at 16.80 chs., course S.70°W.;
 asc.
- 40.00 Set an iron post 3 ft. long, 1 in. diam., 26 ins. in the
 ground for $\frac{1}{4}$ sec. cor., with brass cap marked:



and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W.
 of cor. This cor. is 15 ft. above wash.

- 40.50 Top of spur, 20 ft. above $\frac{1}{4}$ sec. cor., projects S.80°W.;
 desc.
- 44.30 Bottom of draw, 45 ft. below top of spur, course S.80°W.;
 asc.
- 47.00 Top of spur, 25 ft. above bottom of draw, projects S.80°W.