

Chains.

and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor. This cor. is 15 ft. below spur.

42.60 Bottom of draw, 45 ft. below ¼ sec. cor., course N.80°W.; asc.

48.90 Top of spur, 85 ft. above draw, projects N.80°W. 25 chs.; desc.

52.50 Bottom of draw, 65 ft. below spur, course N.80°W.; asc.

53.90 Top of spur, 25 ft. above draw, projects N.80°W. 5 chs.; desc.

58.00 Bottom of draw, 70 ft. below spur, course N.70°W.; asc.

64.90 Top of spur, 145 ft. above draw, projects N.80°W. 15 chs.; desc.

68.10 Bottom of draw, 90 ft. below spur, course N.70°W.; asc.

74.20 Top of spur, 105 ft. above draw, projects W. 10 chs.; desc.

80.00 Set an iron post 3 ft. long, 2 ins. in diam., 24 ins. in the ground for cor. of secs. 25, 30, 31 and 36, with brass cap marked:

T28N	
R36E	R37E
S25	S30
S36	S31
1917	

and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor. This cor. is 30 ft. below spur.

Land; low and rolling mountainous with outcroppings of quartzite and volcanic formation.

Soil; rocky, light and sandy 12 ins. to 18 ins. deep to solid rock.

Timber; few scattering cedars and pinon pine.

Undergrowth; dense shadscale and scattering grease wood.

Western exposure. Drainage W. Fair growth of bunch grass.

S. bet. secs. 31 and 36.

Over rolling land, through dense shadscale and scattering grease wood; desc.