

Chs.

From the cor. of secs. 1, 2, 35 and 36 on the S. bdy. of the Tp., which is an iron post, 3 ins. diam., 16 ins. above ground, firmly set, surrounded by a mound of stone, properly marked and witnessed by a mound of stone W. of cor.,

N. on a random line bet. the E. two ranges of secs. in T. 23 N., R. 48 E., setting temp. points at intervals of 40 chs., until at

482.11

Intersect the N. bdy. of the Tp., 16 lks. W. of the old cor. of secs. 1, 2, 35 and 36, which is an iron post, 3 ins. diam., 26 ins. above ground, firmly set in a mound of stone, properly marked and witnessed by a mound of stone W. of cor.

The bearing of this line is therefore N.0°01'E.

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., heretofore described,

N.0°01'E. on a governing subdivisional line bet. the two E. ranges of secs. of T. 23 N., R. 48 E., bet. secs. 35 and 36.

Over rolling mountainous land, through dense sagebrush, rabbit brush and scattering service berry bushes; asc.

3.00 Top of spur, 15 ft. above sec. cor., projects SE.; desc.

7.50 Dry creek, 8 lks. wide 2 ft. deep, in the bottom of ravine, 105 ft. below top of spur, course S.80°E.; asc. S. slope.

24.20 Top of spur, 245 ft. above creek, projects E. 20 chs.; desc.

35.00 Bottom of draw, 120 ft. below top of spur, course E.; asc.

40.00 Set an iron post 3 ft. long, 1 in. diam., 26 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked: