


Chs.

- 82.20 Intersect the N. bdy. of the Tp., 43 lks. E. of the cor. of secs. 3, 4, 33 and 34, which is an iron post, 3 ins. diam., 20 ins. above ground and in a mound of stone, firmly set, properly marked and witnessed by bearing trees and a mound of stone W. of cor. S.0°18'E., on a true line bet. secs. 3 and 4. Over steep and rough mountainous land, through heavy timber and a medium growth of short sagebrush and service berry bushes; desc.
- 9.70 Bottom of draw, 110 ft. below sec. cor., course W.; asc.
- 12.50 Top of spur, 60 ft. above bottom of draw, projects W. 30 chs.; desc.
- 26.00 Bottom of ravine, 225 ft. below top of spur, course N.80°W.; asc.
- 33.40 Top of spur, 245 ft. above bottom of ravine, projects W. 30 chs.; desc.
- 42.20 Set an iron post 3 ft. long, 1 in. diam., 26 ins. in the ground for  $\frac{1}{4}$  sec. cor., with brass cap marked:



from which

A pinon pine, 14 ins. diam., bears N.39°45'E., 107 lks. dist., marked  $\frac{1}{4}$  S 3 B T.

A pinon pine, 16 ins. diam., bears S.71°W., 24 lks. dist., marked  $\frac{1}{4}$  S 4 B T.

This cor. is 215 ft. below top of spur.

- 45.20 Bottom of draw, 50 ft. below  $\frac{1}{4}$  sec. cor., course N.60°W.; asc.
- 45.20 Leave heavy timber, bears E. and W.
- 54.20 Enter heavy timber, bears E. and W.
- 54.20 Top of spur, 295 ft. above bottom of draw, projects W. 30 chs.; desc.