

74.

Subdivision of T. 23 N., R. 48 E.

Chs.

Undergrowth; dense sagebrush, yellow top and grease wood,
S. 66.70 chs.

No timber. Fair grazing. Limestone formation.

Drains and slopes gently to the W.

From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of
the Tp., which is an iron post, 3 ins. diam., 16 ins. a-
bove ground, firmly set in a mound of stone, properly
marked and witnessed by a mound of stone W. of cor.,
N.0°02'W. bet. secs. 31 and 32.

Over mountainous land, through scattering sagebrush and
rabbit brush; asc. gradually.

4.60 Top of spur, 35 ft. above sec. cor., projects NW. 3 chs.;
desc.

9.40 Foot of mountain, 85 ft. below top of spur, bears NW. and
SE., enter valley; desc. over rolling land.

40.00 Set an iron post 3 ft. long, 1 in. diam., 26 ins. in the
ground for $\frac{1}{4}$ sec. cor., with brass cap marked:

S 31		S 32
1917		

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W.
of cor. This cor. is 160 ft. below foot of mountain.

80.00 Set an iron post 3 ft. long, 2 ins. diam., 24 ins. in the
ground for cor. of secs. 29, 30, 31 and 32, with brass
cap marked:

T23N		R48E
S30		S29
S31		S32
1917		

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W.
of cor. This cor. is 145 ft. below $\frac{1}{4}$ sec. cor.

Land; mountainous, S. 9.40 chs.; rolling valley, N. 70.60
chs.