

## Survey of the North boundary of T. 43 N., R. 35 E.

## Chains

West, on true line bet. secs. 6 and 31.

Desc. W. slope 145 ft. to,

6.60 Ravine, 15 lks. wide, 30 ins. deep, course S., asc. E. slope 230 ft. to,

16.25 Ridge, bears N. and S., desc. SW. slope 20 ft. to,

19.19 Draw, course S., asc. SE. slope 50 ft. to,

28.80 Ridge, bears N. and S., desc. SW. slope 115 ft. to,

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 10 ins. in ground, in a mound of stone, for  $\frac{1}{4}$  sec. cor., with brass cap marked,

$\frac{1}{4}$  S 31  
S 6

1918 ; raise a mound

of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

Desc. W slope 90 ft. to,

43.22 Draw, course S., asc. abrupt E. slope 65 ft. to,

48.89 Ridge, bears N. and S., over low hills.

54.17 Draw, course S., asc. E. slope 20 ft. to,

58.87 Ridge, bears N. and S., desc. W. slope 75 ft. to,,

63.24 A point, directly South of the original corner of Ts. 43 and 44 N., Rs. 34 and 35 E. At this point,

Set an iron post, 3 ft. long, 3 ins. in dia., 16 ins. in ground, to bedrock, in a mound of stone, for cor. of

T. 44 N., R. 35 E., with brass cap marked,

T 44 N  
R 35 E  
S 31

1918

; raise a mound

of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, NE. of cor.

Thence,

North on true line bet. secs. 6 and 31.

3.70 The original corner of Ts. 43 and 44 N., Rs. 34 and 35 E., which is a granite stone, 24x12x6 ins., lying on top of a mound of stone, marked with 6 notches on the N., E., S., and W., edges. I obliterate the marks on the S. and