

Survey of the North boundary of T. 43 N., R. 35 E.

Chains.

E., edges to make this corner refer to T. 44 N., R. 34 E., only. I re-set the stone, 15 ins. in ground, and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, NW. of cor.

Thence,

West, on true line bet. secs. 6 and 36.

23.86

The cor. of Ts. 43 N., Rs. 34 and 35 E., previously established and described.

Land, rolling hills.

Soil, heavy, compact clay loam, very rocky.

Undergrowth, sagebrush.

Subdivisions of T. 43 N., R. 35 E.

From the cor. of secs. 1, 2, 35 and 36, on the south bdy. of the township, previously described,

N.0°01'W., on true line bet. secs. 35 and 36.

Asc. SE. slope 58 ft. to,

9.96

Ridge, bears NW. and SE., desc. NE. slope 52 ft. to,

23.90


Head of a draw, course E., asc. SE. slope 45 ft. to,

38.91

Ridge, bears NE. and SW., desc. N. slope 5 ft. to,

40.00

Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in ground, for 1/4 sec. cor., with brass cap marked,




; raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

Desc. a rolling NE. slope 74 ft. to,

80.00

Set an iron post, 3 ft. long, 2 ins. in dia., 24 ins. in ground, for cor. of secs. 25, 26, 35 and 36, with brass cap marked,



1918 ; raise a mound of

stone, 2 ft. base, 1 1/2 ft. high, W. of cor.