Chains From the cor. of Ts. 11 N., Rs. 29 and 30, E., previously described,
West, on true line on the north boundary of sec. 1.

Along a very broken N. slope, desc. 236 ft. to, 37.11

25.65 Spur, falls N.20 W. at the wave . We seemed

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in ground, for $\frac{1}{4}$ sec. cor., with brass cap marked,

1 S 1

1918

; dig pits, 18x18x12

ins. E. and W. of cor. 3 ft. dist.

80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 24 ins. in ground, for cor. of secs. L and 2, with brass cap marked,

TILNR29 E

1,918

; raise a mound of

stone, 2 ft. base, $1\frac{1}{2}$ ft. high. S. of cor.

Land, rolling hills.

Soil, deep, gravelly sand.

Undergrowth, greasewood.

West, on true line botthe north boundary of sec. 2.

3.40.00 Set an iron post, 3 ft. long, l.in. in dia., 26 ins. in ground, for $\frac{1}{4}$ sec. cor., with brass cap marked,

1 S 2

1918

; dig pits, 18x18x12

sins, E. and W. of cor. 3 ft. dist.

- 41.55 Road, bears NE. and SW., in a ravine, course SW.
- 43.59 The original cor. of Ts. 11 and 12 N., Rs. 29 and 30 E.,
 which is an old redwood post, 12 ins. above ground,
 marked and witnessed as described by the surveyor-general. I obliterate the markings on the SE. and SW. edges
 to change it to refer to Ts. 12 N., Rs. 29 and 30 E.,
 only.