


Dependent Resurvey of a portion of the subdivisions of T. 42 N., R. 39 E.

Chains

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 15 ins. in ground, to bedrock, in a mound of stone, for $\frac{1}{4}$ sec. cor. with brass cap marked,



1918 ; raise a mound of

stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

44.13 The original $\frac{1}{4}$ sec. cor., bet. secs. 4 and 5, which is a stone, firmly set, and marked and witnessed as described by the surveyor-general. I turn this stone, so that the $\frac{1}{4}$ will face to the East, and move the mound to the East, so that the cor. will now refer to sec. 4 only.

Subdivisions of T. 42 N., R. 39 E.


From the cor. of secs. 5, 6, 31 and 32 on the south bdy. of the township, which is a 3 in. iron post, marked and witnessed as described by the surveyor-general. N.0°01'E., on true line bet. secs. 31 and 32.

Asc. S. slope 108 ft. to,

9.84 Spur, falls E., desc. NE. slope 330 ft. to,

25.31 Stream, 15 lks. wide, 3 ins. deep, course E., asc. 320 ft to,

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in ground, for $\frac{1}{4}$ sec. cor., with brass cap marked,



1918 ; raise a mound of

stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

54.00 Spur, falls E., desc. 313 ft. to,

68.03 Stream, 15 lks. wide, 3 ins. deep, course E., asc. SW. slope 320 ft. to,

80.00 Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in the ground for cor. of secs. 29, 30, 31 and 32 with brass cap mkd.;