

Survey of the Seventh Standard Parallel North, thru R.31 E.

Chains. The old standard cor. of Tp.36 N., Rs.31 and 32 E. is a stone mound, 2 ft. base, 1 ft high, with stone 8x6x6 ins.

in center of mound and marked as described by the surveyor general. The whole mound was nearly covered with sand. Alongside of the marked stone, I set an iron post 3 ft. long, 3 ins. diam., 24 ins. in the ground for standard cor. of Tp.36 N., Rs.31 and 32 E., with brass cap marked

SC  
T36N | R31E | R32E

S36 | S31

1918

and raise a mound of stone 2 ft. base,  $\frac{1}{2}$  ft. high, N. of cor., from which

A juniper, 8 ins. diam., bears N.33° E., 30 lks. dist.,

marked T36N R32E S31 SC BT

A juniper, 6 ins. diam., bears N.6° W., 1.52 chs. dist.,

marked T36N R31E S36 SC BT

Thence

West, on the Seventh Standard Parallel North, on the S. bdy. of sec. 36.

Asc. 65 ft. over NE. slope of sand ridge.

Thru scattering juniper timber.

2.50 Top of sand ridge sloping N. Desc. 75 ft. over rolling NW. slope. Leave scattering juniper, bears N. and S.

40.00 Set an iron post 3 ft. long, 1 in. diam., 26 ins. in the ground for  $\frac{1}{2}$  sec. cor., with brass cap marked

SC  
 $\frac{1}{2}$ S36

1918

dig pits, 18x18x12 ins., E. and W. of cor. 3 ft. dist.

Thence over gentle SW. slope.

53.00 Draw, course S.30° W. Asc. 65 ft. over E. slope.

80.00 Set an iron post 3 ft. long, 2 ins. diam., 24 ins. in the ground for standard cor. of secs. 35 and 36, with brass cap marked

SC  
T36N | R31E  
S35 | S36

1918