

Dependent Resurvey of a Portion of the South bdy. of T.44 N., R.30 E.

Chains.

65.00 Base of foot hills bearing N. and S. Asc. 50 ft. over E.

slope.

78.07 Allowing for convergency, as per instructions, set an iron post 3 ft. long, 2 ins. diam., 24 ins. in the ground for cor.

of secs. 34 and 35, with brass cap marked

T44N	R30E
S34	S35

1918

1918

dig pits, 18x18x12 ins., in each sec., 5 1/2 ft. dist. from cor.

80.00 Record distance for the old cor. of secs. 2, 3, 34 and 35.

Set an iron post 3 ft. long, 2 ins. diam., 24 ins. in the ground for cor. of secs. 2 and 3 on the N. bdy. of T.43 N.,

R.30 E., with brass cap marked

S3	S2
T43N	R30E

1918

dig pits, 18x18x12 ins., in each sec. 5 1/2 ft. dist. from cor.

Land, gentle East slope and nearly level.

Soil, deep sandy clay loam, medium texture, clay subsoil.

East 40 chains slightly alkaline, no rock.

Undergrowth, medium sage brush and grease wood.

Survey of S. bdy. of T.44 N., R.30 E.

From the cor. of secs. 34 and 35 on the S. bdy. of Tp., heretofore described

West, on the S. bdy. of sec. 34.

1.93 The cor. of secs. 2 and 3 on the N. bdy. of T.43 N., R.30 E., heretofore described. Asc. 275 ft. over E. slope.

14.38 Spur, slopes NE. Asc. 425 ft. over steep NE. slope.

40.00 Set an iron post 3 ft. long, 1 in. diam., 26 ins. in the ground for 1/4 sec. cor., with brass cap marked

S34

1918