

Survey of the S.bdy. of T.44 N., R.30 E.

Chains.
 10.00 West, on the S.bdy. of sec. 32. Over broken land.
 23.95 Spur, slopes N. Desc. 850 ft. over NW. slope.
 40.00 Set an iron post 3 ft. long, 1 in. diam., 26 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked
 $\frac{1}{4}$ S32
 1918
 raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
 52.75 Draw, course N. Asc. 25 ft. over E. slope.
 60.54 Stream, 3 lks. wide, 3 ins. deep, clear water, rock bottom, course NE. Aspen trees of fringe banks of stream. Asc. 380 ft. over E. slope.
 63.52 Spring of clear water, bears S. 75 lks. dist.
 64.32 " " " " N. 2.50 chs. dist.
 80.00 Set an iron post 3 ft. long, 2 ins. diam., 24 ins. in the

ground for cor. of secs. 31 and 32, with brass cap marked

T44N	R30E
S31	S32

1918

raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
 Land, mountainous.
 Soil, rocky and sandy on slopes with exposed ledges; deep black alluvial clay loam in draws and canyons.
 Undergrowth, sage and shadscale.

West, on the S.bdy. of sec. 31.

Asc. 10 ft. over E. slope.

2.19 Thence over gentle N. slope of bench land.
 12.14 West edge of bench land. Asc. 135 ft. over E. slope.
 18.61 Ridge, bears N. and S. Desc. 500 ft. over W. slope.
 40.00 Set an iron post 3 ft. long, 2 ins. diam., 26 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked

T44N	R30E
S31	S32

1918

raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.