

Survey of the subdivision of T.45 N., R.30 E.

Chains.

from which a granite rock, 3x4x5 ft. above ground, bears East, 1 lk. dist., marked X on W. face. Raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

Asc. 190 ft. over rocky W. slope.

69.50 Rocky ridge, bears N. 20° W. and S. 20° E. Desc. 430 ft. over broken E. slope.

80.02 The cor. of secs. 5, 6, 7 and 8.

Land, mountainous.

Soil, coarse granite sand, shallow and with granite boulders and ledges.

Undergrowth, sage and shadscale.

N. 0° 01' E., on a true line bet. secs. 5 and 6.

Asc. 90 ft. over SE. slope.

15.00 Desc. 10 ft. over NE. slope.

15.41 Gulch, course SE. Asc. 250 ft. over exceptionally rocky S. slope.

40.00 Set an iron post 3 ft. long, 1 in. diam., 20 ins. in the ground to solid rock with mound of stone around post, for $\frac{1}{4}$ sec. cor., with brass cap marked,

$\frac{1}{4}$
S6 | S5

1918

from which

A granite cliff 30 ft. high, facing SE, bears NW., 52 lks. dist., marked X

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Asc. 970 ft. over rocky S. slope.

46.00 Enter mountain mahogany, bears E. and W.

83.00 Ridge, bears E. and W. Desc. 110 ft. over N. slope.

87.89 Intersect Ninth Standard Parallel N. 15.30 chs. West of the standard $\frac{1}{4}$ sec. cor. S. of sec. 32, which is an iron post, 1 in. diam., extending 12 ins. above ground, marked and witnessed as described by the surveyor general. At point of intersection set an iron post, 3 ft. long, 2 ins.