

Survey of the subdivision of T.45 N., R.30 E.

Chains.	Asc. 760 ft. over broken W. and SW. slope.
80.00	The cor. of secs. 4, 5, 8 and 9.
	Land, mountainous.
	Soil, coarse, shallow granite sand, boulders and ledges.
	Undergrowth, sage and shadscale.
	N. 0° 02' E., on a true line bet. secs. 4 and 5.
	Asc. 60 ft. over SW. slope.
6.50	Ridge, bears E. and W. Desc. 110 ft. over N. slope.
16.00	Thence over E. slope.
25.30	Enter mountain mahogany, bears E. and W. Asc. 55 ft. over SE. slope.
30.00	Leave mahogany, bears E. and W. Desc. 115 ft. over NE. slope.
39.85	Gulch, course S. 75° E.
40.00	Set an iron post 3 ft. long, 1 in. diam., 6 ins. in the ground to solid rock, with mound of stone around post for $\frac{1}{4}$ sec. cor., with brass cap marked
	S5 $\frac{1}{4}$ S4
	1918
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
	Asc. 405 ft. over S. slope.
52.00	Enter scattering mahogany, bears E. and W.
58.95	Ridge, bears NW. and SE. Desc. 35 ft. over NE. slope.
65.80	Asc. 75 ft. over SE. slope. Leave mahogany, bears E. and W.
73.65	Ridge, bears NE. and SW. Desc. 145 ft. over N. slope.
77.00	Thence over E. slope.
82.80	Ridge, bears E. and W. Desc. 130 ft. over N. slope.
87.89	Intersect Ninth Standard Parallel N. 15.27 chs. W. of the standard $\frac{1}{4}$ sec. cor. S. of sec. 33, which is an iron post, 1 in. diam., extending 12 ins. above ground, with brass cap marked and witnessed as described by the surveyor general. At point of intersection set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground for closing cor. secs. 4 and 5, with brass cap marked