

Independent Resurvey, Range Line, T. 12 S., Bet. Rs. 68 and 69 E.

Chains

T12S
R68E R69E

$\frac{1}{4}$

S12 S7

1934

No suitable accessory;

Cor. set on point of spur from E.

Continue over mountainous country, through medium dense undergrowth.

41.80 Draw, course S. 35° W.; asc. 290 ft. on a S. slope.

47.70 Spur, projects S. 40° W.; asc. 70 ft. on S. slope.

54.80 Spur, projects W.; desc. 365 ft. along the crest of a N. and S. ridge sloping to the north.

75.80 N. end of ridge; desc. 240 ft. on steep N. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for the cor. of secs. 1, 6, 7, and 12, with brass cap mkd.

This cor. is situated at the foot of ridge.

T12S
R68E R69E

S1 S6

S12 S7

1934

raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.

Land, mountainous.

Soil, gravelly clay; 3rd rate.

Undergrowth, buckbrush, creosote, cacti, mountain rush; gramma and sand grasses.

No timber.

North, on true line bet. secs. 1 and 6.

Over rolling country, through medium dense undergrowth; desc. 40 ft.

2.50 Wash, course W.; asc. 160 ft. on S. slope.

9.80 Spur, projects W.; desc. 250 ft. on a NW. slope.

22.80 Draw, course N. 60° W.; desc. 90 ft. on a NW. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

T12S
R68E R69E

$\frac{1}{4}$

S1 S6

1934