

Independent Resurvey, Range Line, T11S., Bet. Rs. 68 and 69 E.

Chains	
	Asc. 25 ft. on a SE. slope.
41.90	Spur, projects E. about 5 chs.; desc. 115 ft. on NE. slope.
65.70	Wash, course S. 70° E.; asc. 65 ft. on SE. slope.
77.80	End of spur projecting from W.; desc. 25 ft.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for the cor. of secs. 1, 6, 7, and 12, with brass cap mkd.

T11S	
R68E	R69E
S1	S6

S12	S7
1934	

raise a mound of

stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, steep rolling.
 Soil, gravelly clay; 3rd rate.
 Undergrowth, buckbrush, creosote, cacti, mountain rush;
 gramma and sand grasses.
 No timber.

North, on true line bet. secs. 1 and 6.

Over rolling country, through medium dense undergrowth;
 desc. 45 ft. on NE. slope.

3.70	Wash, course S. 60° E.; asc. 65 ft. on a SE. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for sec. cor., with brass cap mkd.

¼	
S1	S6
1934	

raise a mound of

stone, 2 ft. base, 1½ ft. high, W. of cor.

Continue over rolling country; desc. 60 ft. on a slight
 NE. slope to the sec. cor.

49.20	Wash, course E.
51.90	Small divide between washes.
53.90	Wash, course E.
80.00	Set an iron post, 3 ft. long, 3 ins. diam., 18 ins. in the ground to solid rock, in a mound of stone, for the cor. of Tps. 10 and 11 S., Rs. 68 and 69 E., with brass cap mkd.