

## Independent Resurvey, Range Line, T11S., Bet. Rs. 69 and 70 E.

## Chains

No suitable accessory.

Continue over rolling country; desc. 20 ft.

51.60 Wash, course SE.

57.90 Old road, bears N. 40° W. and S. 40° E.; asc. 5 ft.

62.10 Wash, course SW., same wash as at 51.60 ch. pt.; asc. 75 ft. on SE. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 22 ins. in the ground to solid rock, in a mound of stone, for the cor. of secs. 1, 6, 7, and 12, with brass cap mkd.

T11S

R69E R70E

S1 S6

S12 S7

1934

raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, rolling.

Soil, gravelly clay; 3rd rate.

Undergrowth, buckbrush, creosote, cacti, mountain rush; gramma and sand grasses.

No timber.

North, on true line, bet. secs. 1 and 6.

Over rolling country, through medium dense undergrowth; asc. 100 ft. on a SE. slope to the ¼ sec. cor.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to solid rock, for ¼ sec. cor., with brass cap mkd.

S1 S6

1934

Post over a cross (X) on solid rock, and in a mound of stone.

This cor. is situated at the foot of ridge bearing NE. and SW.; asc. 130 ft. on a SE. slope.

61.50 Ridge, bears NE. and SW.; desc. 120 ft. on a NW. slope.

80.00 Set an iron post, 3 ft. long, 3 ins. diam., 27 ins. in the ground, for cor. of Tps. 10 and 11 S., Rs. 69 and 70 E., with brass cap mkd.

T10S

R69E R70E

S36 S31

S1 S6

T11S

1934

raise a mound of