

SUBDIVISION OF T. 10 S., R. 68 E.

Chains

2.40 Spur, projects NE.; desc. 30 ft.

6.35 Wash, course NE.; start up gradual E. slope, asc. 230 ft.

23.20 Draw, course N. from 5 chs. S.; asc. 205 ft. on E. slope.

33.10 Ridge, bears N. and S.; desc. 215 ft. on a steep, broken W. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to solid rock, in a mound of stone to top, for 1/4 sec. cor., with brass cap mkd.

S19

1/4

S30

1934

A rock 4x6x6 ins. mkd. with a cross (X) deposited at base of post.

Continue along W. slope; desc. 440 ft.

71.80 Wash, course N.; asc. 50 ft.

74.00 Top of raise bearing N. and S.; desc. 75 ft. on W. slope.

80.00 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to solid rock, in a mound of stone to top, for the cor. of lots 7 and 8 sec. 19, and lots 1 and 2 sec. 30, with brass cap mkd.

T10S R68E

S19

7/8

2/1

S30

1934

A limestone 3x4x6 ins. mkd. with a cross (X) deposited at base of post.

Continue line, desc. 20 ft.

85.20 Draw, course N. 30° W., asc. 100 ft. along NE. slope.

93.10 Spur, projects N. 10° E.; desc. 45 ft. on NW. slope.

97.31 Intersect E. bdy. T10S., R67E., N. 0° 10' W., 17.40 chs. dist. from the cor. of secs. 25 and 36, which is a 3 in. iron post mkd. and witnessed as described in the official record, this cor. remarked to refer to R67E only.

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground to solid rock, in a mound of stone to top, for the closing cor. of secs. 19 and 30, T10S., R68E, with brass cap mkd.

T10S

R67E

R68E

S19 c

S25

S30 c

1934

A limestone 4x4x6 ins. mkd. with a cross (X) deposited at base of post.