

SUBDIVISION OF T. 10 S., R. 68 E.

Chains

65.60 Wash, course N. 10° W.

80.00 Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to solid rock, in a mound of stone to top, for the cor. of lots 10 and 11 sec. 6, and lots 1 and 2 sec. 7, with brass cap mkd.

T10S R68E

S6

10 | 11

2 | 1

S7

1934

Cross (X) cut into solid rock at base of post.

Continue line; desc. 45 ft.

88.85 Wash, course N.; asc. 60 ft.

97.63 Intersect the E. bdy. of T10S., R67E., N. 0° 08' W., 17.32 chs. dist. from the cor. of secs. 12 and 13, R67E., which is a 3 in. iron post mkd. and witnessed as described in the official record, this cor. re-marked to refer to T10S., R67E., only.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for the closing cor. of secs. 6 and 7, T10S., R68E., with brass cap mkd.

T10S

R67E

R68E

S6 C

S12

S7 C

1934

of stone 2 ft. base, 1½ ft. high, E. of cor. raise a mound

Land, rolling.

Soil, shallow sandy loam on gravel; 3rd rate.

Undergrowth, blackbrush, mountain rush, creosote, cacti.

Guyette grass and sand grass.

No timber.

From the cor. of secs. 5, 6, 7, and 8,
N. 0° 09' W., on a random line bet. secs. 5 and 6.

40.00 Set temp. ¼ sec. cor.

80.00 Intersect N. bdy. of Tp. 18 lks. E. of the cor. of secs. 5, 6, 31 and 32.

Thence

S. 0° 17' E. on true line bet. secs. 5 and 6.

Over rolling country, through medium dense undergrowth;
asc. 80 ft. on general N. slope.

4.70 Road, bears E. and W. (Caliente Highway).

20.00 Enter wash, course NE. from S.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for ¼ sec. cor., with brass cap mkd.