

Subdivision of T. 44 N., R. 58 E.

Chains	
61.90	Top of ledge, 60 ft. high on spur, projecting SE.; desc. 190 ft. over rocky SW. slope, through very scattering mahogany.
69.00	Small draw, drains SE. from N.; asc. 390 ft. over E. slope.
80.32	The cor. of secs. 2, 3, 10, and 11. Land, rough mountainous. Soil, gravelly loam; 3rd rate. Timber, mahogany, pine and balsam. Undergrowth, sagebrush, manzanita, deer brush, and grouse brush. Grazing, poor to fair.
	N. 0°01' W., bet. secs. 2 and 3. Over mountainous land, through scattering mahogany and medium dense undergrowth; asc. 145 ft. over rocky SE. slope.
12.30	Spur ridge, bears N. 10° E. and S. 10° W.; desc. 165 ft. to 26.50 ch. point; desc. NW. slope.
22.10	Slope changes to W.
26.50	Head of ravine, drains SW.; asc. 220 ft. to 40.00 ch. point over rocky SW. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., on mark (X) on solid rock, in a mound of stone, base 5 ft. for the $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S3 S2 1928
	from which A pine, 25 ins. diam., bears N. 67° E., 161 lks. dist., mkd. $\frac{1}{4}$ S 2 B T.
	Continue ascent 155 ft. over SW. slope.
41.20	Rocky spur, projects S. 60° W.; desc. 590 ft. to 81.96 ch. point; desc. across W. slope.
57.20	Rocky spur; projects W. about 8 chs. thence SW.; desc. NW. slope.
66.70	Spur, projects NW.; desc. N. slope.
70.00	Enter medium pine and balsam, bears NW. and SE.
81.96	Intersect the N. bdy. of the Tp. Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground, and in a mound of stone to top, for closing cor. of secs. 2 and 3 with brass cap mkd.
	T45NR58E S34 S3 S2 CC T44N 1935