


Subdivision of T. 44 N., R. 58 E.

Chains
 19.60 Spur, projects S. 20° W.
 25.50 Top of ascent, bears NW. and SE.; desc. along broken NW. slope 115 ft.
 31.30 Enter dense aspen, bears NE. and SW. along top of rocky spur projecting NW. From this point, a small group of springs draining SW., bears W. 5 chs. dist.; desc. along NW. slope.
 37.10 Leave timber, bears E. and W.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground; for $\frac{1}{2}$ sec. cor., with brass cap mkd.



Deposit an igneous rock, 6x5x4 ins., mkd. with a cross (X), at base of post.

No suitable bearing trees available.

This cor. is situated at edge of dense scrub aspen timber thicket, edge bears E. and W.

Continue decent over NW. slope through dense aspen thicket.


44.10 Leave aspen, bears E. and W. along top of spur projecting N. 80° W.; continue descent over NW. slope through scattered aspen thickets.

49.50 Draw, 395 ft. below spur at 31.30 ch. pt., drains S. 80° W.; asc. 325 ft. along a SW. slope through scattering undergrowth and no timber.

66.90 Top of ascent, bears E. and W.; desc. 40 ft. along general W. slope.

82.05. Intersect the N. bdy. of the township.

Set an iron post, 3 ft. long, 2 ins. diam., over a cross (X) in solid rock, and in a mound of stone, 6 ft. base, to top of post, for closing cor. of secs. 4 and 5, T. 44 N., R. 58 E., with brass cap mkd.



from which,

The exact center of a cross (X) cut in the middle of the SW. edge of a malpais rock, 8x8x4 ft. bears N. 52°45' E., 11 lks. dist. Rock is mkd.

B0

From the point of intersection, the cor. of secs. 32 and 33; T. 45 N., R. 58 E., heretofore described, bears East, 5.90 chs. dist.

Land, rolling to rough mountainous.

Soil, shallow and rocky; 4th rate.

Undergrowth, sagebrush. Native grasses and shrubs.