

Subdivision of T. 44 N., R. 58 E.

Chains

N. 89°57' W., on true line bet. secs. 6 and 7.

Over rolling mountains, through medium dense undergrowth and scattering timber; desc. 250 ft. over a W. slope.

8.30 Stream, branch of 76 Creek, about 4 lks. wide and 2 ins. deep, course S. 10° E.; this stream is in the bottom of a draw draining S. 19° E.; asc. 70 ft. over an E. slope.

15.50 Low conical hill; on low spur projecting S.; desc. a slight W. slope.

23.50 Draw, drains S. 10° E.; asc. 300 ft. over an E. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

S6

$\frac{1}{4}$

S7

1935

raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

This cor. is situated on a divide ridge bearing N. and S.

Desc. 100 ft. over a NW. slope.

45.00 Old unused road, bears N. and S.

45.40 Draw, drains S. 10° W.; asc. 70 ft. to the 67.60 ch. pt.; asc. along a SE. slope.

55.40 Spur, projects SW.; continue ascent over an E. slope.

67.60 Spur, projects SW.; desc. 130 ft. over a W. slope.

79.12 Intersect the W. bdy. of the Tp.

At the point of intersection,

Set an iron post, 3 ft. long, 2 ins. diam., 14 ins. in the ground, and in a mound of stone, 3½ ft. base, to top of post, for the closing cor. of secs. 6 and 7, with brass cap mkd.

T44N

R57E

R58E

S12

S 6 C

S 7 C

1935

No suitable bearing trees available in either section.