

Resurvey of the 9th Standard Parallel North in Range 58 East

Chains

Independent resurvey of the 9th Standard Parallel North in Range 58 East, superseding the survey executed by Dennis Scully, United States Deputy Surveyor in 1896.

Beginning at the standard corner of T. 46 N., Rs. 58 and 59 E., an iron post, 3 inches in diameter, firmly set, properly marked and witnessed as described in the official record.

West, with the establishment of the 9th standard parallel north, along the south boundary of section 36, T. 46 N., R. 58 E., on a transit line describing the tangent, starting at the township corner and bearing west.

Over mountainous land, through medium dense timber and a scant undergrowth, descend 90 ft. along a SW. slope.

5.70 Fall Creek, stream of good water, 8 links wide and 5 inches deep, flows NW., ascend 110 ft. along a NE. slope.

11.60 Spur, slopes NW., descend 20 ft. along a SW. slope.

29.80 Draw, drains NE., ascend 190 ft. along a SE. slope.

40.00 On the tangent:

Set an iron post, 3 ft. long, 1 in. diameter, 18 ins. in the ground to solid rock, and in a mound of stone, for standard 1/4 sect. cor., with brass cap mkd.

SC
1/4S36

1936

from which,

A balsam fir, 18 ins. diameter, bears N 74° 00' E., 39 lks. dist., mkd. SC 1/4S36BT.

A fir, 5 ins. diameter, bears N 18° 15' W., 52 lks. dist. mkd. SC 1/4S36BT.

No trace of the original standard cor. could be found.

Asc. 1120 ft. over SE. and E. slopes.

78.50 Spur, slopes NE., descend 110 ft. along a rocky NW. slope.

80.00 North 1 link from the tangent,
Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to solid rock, with a trachyte stone, 10x6x4 ins., mkd. X deposited at the base, and in a mound of stone, for standard cor. of secs. 35 and 36, with brass cap mkd.

SC
T46NR58E
S35 | S36

1936

No trace of the original standard cor. could be found.