

SUBDIVISION OF T. 45 N., R. 58 E.

Chains

39.90 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to solid rock, and in a mound of stone, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

S2

$$\frac{1}{4}$$

 S11
 1936

from which,

A pine, 3 ins. diam., bears S. $5\frac{1}{4}^{\circ}$ W., 77 lks. dist., mkd. BT.

A fir, 4 ins. diam., bears N. $56\frac{3}{4}^{\circ}$ E., 215 lks. dist., mkd. $\frac{1}{4}$ S2 BT.

Asc. along a NE. slope.

66.60 Spur, slopes N.; desc. 350 ft. over a W. slope.

79.80 The cor. of secs. 2, 3, 10 and 11.

Land, rolling mountain slopes, general NW. exposure and drainage.

Soil, gravelly to rocky loam, 3rd rate.

Timber, fir, pine and mahogany; undergrowth, sagebrush and weeds. Native grasses.

Good grazing.

N. $0^{\circ}02'$ W. on true line between secs. 2 and 3.

Over mountainous land, through a scattering timber and a medium dense undergrowth; desc. 580 ft. along a general NW. slope to the draw.

4.70 Spur, slopes W.; continue descent.

25.50 Draw, drains W., stream of good water, 5 lks. wide and 2 ins. deep, in bottom; asc. 350 ft. over a S. slope.

34.70 Small spur, slopes W.; continue ascent.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to solid rock, and in a mound of stone, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{1}{4}$$

 S3 | S2
 1936

from which,

A mahogany, 6 ins. diam., bears S. $16\frac{3}{4}^{\circ}$ E., 74 lks. dist., mkd. $\frac{1}{4}$ S2 BT.

A pine, 5 ins. diam., bears S. $61\frac{1}{4}^{\circ}$ W., 20 lks. dist., mkd. $\frac{1}{4}$ S3 BT.

Continue ascent along a SW. slope.

47.29 Intersect the 9th Standard Parallel North.