

SUBDIVISION OF T. 45 N., R. 58 E.

Chains

3.50 Spur, slopes E. about 5 chs. to end; desc. 40 ft. along a NE. slope.

6.10 Draw, drains E.; asc. 280 ft. along a SE. slope.

17.10 Spur, slopes E.; desc. 230 ft. along a NE. slope.

26.30 Draw, drains SE., small stream of good water in bottom; asc. 430 ft. along a S. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 9 ins. in the ground to solid rock, and in a mound of stone, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   
S5 | S4  
1936

from which,

A mahogany, 5 ins. diam., bears S.46°E., 89 lks. dist., mkd.  $\frac{1}{4}$  S4 BT.

A mahogany, 8 ins. diam., bears S.47 $\frac{1}{2}$ °W., 47 lks. dist., mkd.  $\frac{1}{4}$  S5 BT.

Asc. 240 ft. along a S. slope.

47.07 Intersect the 9th Standard Parallel North.

Set an iron post, 3 ft. long, 2 ins. diam., 4 ins. in the ground to solid rock, and in a mound of stone, for closing cor. of secs. 4 and 5, with brass cap mkd.

T46NR58E.  
S32  
-----  
S5 | S4  
T45NR58E  
CC  
1936

from which

A mahogany, 6 ins. diam., bears S.43 $\frac{1}{2}$ °E., 43 lks. dist., mkd. T45N R58E S4 CC BT.

A mahogany, 5 ins. diam., bears S.65°W., 79 lks. dist., mkd. T45N R58E S5 CC BT.

From point of intersection, the standard  $\frac{1}{4}$  sec. cor. on S. bdy. Sec. 32, T. 46 N., R. 58 E., heretofore described, bears West, 9.92 chs. dist.

Land, rough mountain slopes, SE. drainage and exposure. Soil, gravelly to rocky loam, 3rd rate. Timber, mahogany, aspen, fir and pine; undergrowth, sagebrush and weeds. Native grasses. Good grazing.

Thence, from the cor. of secs. 31 and 32 on the S. bdy. of the tp., an iron post, 2 ins. diam., firmly set, properly mkd. and witnessed as described in the official record.

N.0°04'W. between secs. 31 and 32.