

SUBDIVISION OF T. 45 N., R. 58 E.

Chains

N.0°04'W. on true line between secs. 5 and 6.

Over mountainous land, through scattering timber and a dense undergrowth; asc. 60 ft. along a SW. slope.

4.20 Spur, slopes SE.; desc. 40 ft. along a NE. slope.

16.80 Head of draw draining S.60°E.; asc. 250 ft. along a SE. slope.

31.50 Ridge, bears E. and W., divide between Pine and Bear Creeks; desc. 70 ft. along a NE. slope to the 1/4 sec. cor.

31.81 A pine, 28 ins. diam., on line, marked with two hacks each on N. and S. sides.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.



from which,

A fir, 6 ins. diam., bears N.55 1/2°E., 49 lks. dist., mkd. 1/4 S5 BT.

A fir, 24 ins. diam., bears S.58 1/2°W., 8 lks. dist., mkd. 1/4 S6 BT.

Desc. 70 ft. along a NE. slope.

46.78 Intersect the 9th Standard Parallel North.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for closing cor. of secs. 5 and 6, with brass cap mkd.



from which,

A fir, 7 ins. diam., bears S.47°E., 32 lks. dist., mkd. T45N R58E S5 CC BT.

A fir, 11 ins. diam., bears S.25 1/2°W., 51 lks. dist., mkd. T45N R58E S6 CC BT.

From point of intersection the standard 1/4 sec. cor. on S. bdy. sec. 31, T. 46 N., R. 58 E., heretofore described bears West, 10.28 chs. dist.

Land, rugged mountain slopes, drainage SE. and N. from the ridge at the 31.50 ch. pt.

Soil, gravelly to rocky loam, 3rd rate.

Timber, aspen and fir; undergrowth, sagebrush and weeds.

Native grasses.

Good grazing.