

SUBDIVISION OF T. 45 N., R. 58 E.  
ESTABLISHMENT OF  $\frac{1}{4}$  SEC. COR. ON N. BDY.

75  
329

Chains

At a point 9.86 chs. E. of the standard cor. of secs. 32 and 33, and midway between the closing cors. of secs. 3 and 4, and secs. 4 and 5,

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to solid rock, with a granite stone, 5x5x3 ins., mkd. X deposited at the base, and in a mound of stone, for  $\frac{1}{4}$  sec. cor. of secs. 4 only, with brass cap mkd.

$\frac{1}{4}$  S4  
1936

At a point 10.10 chs. E. of the standard cor. of secs. 31 and 32, and midway between the closing cors. of secs. 4 and 5 and secs. 5 and 6,

Set an iron post, 3 ft. long, 1 in. diam., over a cross X cut into solid rock, and in a mound of stone, for  $\frac{1}{4}$  sec. cor. of sec. 5 only, with brass cap mkd.

$\frac{1}{4}$  S5  
1936

from which,

An aspen, 9 ins. diam., bears S.62 $\frac{1}{2}$ °E., 190 lks. dist., mkd.  $\frac{1}{4}$  S5 BT.

An aspen, 13 ins. diam., bears S.83 $\frac{1}{2}$ °W., 200 lks. dist., mkd.  $\frac{1}{4}$  S5 BT.

At a point 10.28 chs. E. of the standard cor. of T. 46 N. Rs. 57 and 58 E., and 40.00 chs. W. of the closing cor. of secs. 5 and 6,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor. of sec. 6 only, with brass cap mkd.

$\frac{1}{4}$  S6  
1936

from which,

An aspen, 5 ins. diam., bears S.13 $\frac{3}{4}$ °E., 274 lks. dist., mkd.  $\frac{1}{4}$  S6 BT.

An aspen, 5 ins. diam., bears S.7 $\frac{1}{2}$ °W., 276 lks. dist., mkd.  $\frac{1}{4}$  S6 BT.

GENERAL DESCRIPTION

The area surveyed is located along the crest of the divide between the drainage systems of Mary's River and that of the tributaries of the Bruneau River. Most of