

364

SUBDIVISION, T. 46 N., R. 58 E.

Chains
79.88

Intersect the N. bdy. of the Tp.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for the closing cor. for secs. 2 and 3, with brass cap mkd.

T47N R58E

S35

S3	S2
T46N	R58E

CC

1938

raise a mound
of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of cor.

From this point the cor. of secs. 2, 3, 34, and 35, bears West, 5.11 chs. dist.; an iron post, 2 ins. diam., 12 ins. above the ground, mkd. and witnessed, as described in the official record. This cor. will hereafter refer to secs. 34 and 35, only, therefore, I destroy the mound of stone to the W., and alter the cor. monument to read:

T47N R58E

S34 S35

S3

T46N

1918

raise a mound
of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

Land, rolling.

Soil, sandy, rocky clay, 2nd and 3d rate.

Timber, mahogany; undergrowth, sagebrush.

Grazing, good.

From the standard cor. of secs. 33 and 34, on the 9th Standard Parallel, N.; an iron post, 2 ins. diam., 10 ins. above the ground, mkd. and witnessed, as described in the field notes of T. 45 N., R. 58 E.

N. $0^{\circ} 02'$ W., bet. secs. 33 and 34.

Asc. 130 ft. over mountainous land, along a W. slope, thru scattering timber and undergrowth.

10.30 Leave W. slope; desc. 220 ft. over a N. slope.

13.30 Trail, bears E. and W.

18.90 Draw, with flowing water 2 ins. wide, drains S. 80° W.; asc. 310 ft. over a S. slope.

27.00 Leave S. slope; asc. 70 ft. along a W. slope.

34.90 Draw, drains S. 70° W.; asc. 670 ft. over a S. slope.40.00 Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground, to bedrock and in a mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.