

SUBDIVISION, T. 46 N., R. 58 E.

Chains

asc. 1010 ft. over a rocky SE. slope.

80.08 The cor. of secs. 4, 5, 8, and 9.

Land, rolling.

Soil, rocky clay, 3d rate.

Timber, widely scattering aspen and mahogany; undergrowth, sagebrush, snowbrush and native grasses and weeds.

Grazing, good.

N. 0° 03' W., on true line, bet. secs. 4 and 5.

Asc. 180 ft. over rolling land, on a SE. slope, thru scattering undergrowth.

21.80 Spur, slopes E.; desc. 90 ft. along an E. slope.

28.50 Head of draw, drains E.; asc. 90 ft. along an E. slope.

34.50 Top of ascent, bears E. and W.; desc. 40 ft. over broken land, along an E. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground, to bedrock, with a granite stone, 6x4 ins., mkd. X, deposited at base and in a mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
S5 | S4
1938

54.60 Enter dense timber, bears E. and W.

62.00 Leave dense timber, bears E. and W.; enter scattering sliderock.

80.24 Intersect the N. bdy. of the Tp.

Set an iron post, 3 ft. long, 2 ins. diam., on sliderock, and in a mound of stone, 6 ft. base to top, for the closing cor. for secs. 4 and 5, with brass cap mkd.

T47N R58E

S33

S 5 | S 4
T46N | R58E

CC

1938

No accessories.

From this point, the cor. of secs. 4, 5, 32, and 33, bears West, 5.11 chs. dist.; an iron post, 2 ins. diam., 12 ins. above the ground, mkd. and witnessed, as described in the official record. This cor. will hereafter refer to secs. 32 and 33, only, therefore, I destroy the mound of stone to the W., and alter the cor. monument to read: