

1440

## Dependent Resurvey of the West Bdy. of T. 45 N., R. 61 E.

Chains	Thence															
	N. $0^{\circ}47'$ W., with continuous measurement.															
40.00	At point northing 40.00 chs. from the cor. of secs. 7, 12, 13, and 18.															
	Set an iron post, 3 ft. long, 1 in. diam., 22 ins. in the ground to solid rock, in a mound of stone, for the $\frac{1}{2}$ sec. cor. of sec. 12 only, with brass cap mkd.															
	S12															
	1933															
	A rock 5x3x1 ins. mkd. with a cross (X) deposited at the base of the post.															
	Asc. 1510 ft. on a rocky SE. slope through scattered mahogany timber.															
79.36	The cor. of secs. 1, 6, 7, and 12, which is a basalt stone 12x6x5 ins. mkd. with 5 grooves on S. side and 1 groove on N. side, and witnessed by a mound of stone to the W.															
	At cor. point,															
	Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground to solid rock, in a mound of stone, with the original monument alongside, for the cor. of secs. 6 and 7 only, with brass cap mkd.															
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td></td> <td style="text-align: center;">T45N</td> <td></td> </tr> <tr> <td style="text-align: center;">R60E</td> <td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;">R61E</td> <td></td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;">S6</td> <td></td> </tr> <tr> <td style="text-align: center;">S12</td> <td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;">S7</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">1933</td> <td></td> </tr> </table>		T45N		R60E	R61E			S6		S12	S7			1933	
	T45N															
R60E	R61E															
	S6															
S12	S7															
	1933															
	A mahogany, 4 ins. diam., bears N. $10\frac{1}{2}^{\circ}$ E., 71 lks., mkd. S6 BT only.															
	A mahogany, 6 ins. diam., bears S. $74\frac{1}{2}^{\circ}$ E., 54 lks. dist., mkd. T45N R61E S7 BT.															
	Cor. set on a large spur projecting S. $10^{\circ}$ W.															
	Land, rolling and mountainous.															
	Soil, 1st rate in bottoms and wooded sections, shallow elsewhere.															
	Undergrowth, sagebrush and manzanita. Bunch grass.															
	Timber, aspen and mahogany.															
	Grazing, good.															
	N. $0^{\circ}27'$ W., along the W. bdy. of sec. 6.															
	Over mountainous country.															
.64	At point northing 80.00 chs. from the cor. of secs. 7, 12, 13, and 18.															
	Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground to solid rock, in a mound of stone, for the cor. of secs. 1 and 12 only, with brass cap mkd.															