

Subdivision of T. 45 N., R. 60 E.

Chains

from which

An aspen, 10 ins. diam., bears S. 67°45' E., 24 lks. dist., mkd. $\frac{1}{4}$ S 1 BT.

An aspen, 5 ins. diam., bears S. 88 $\frac{1}{4}$ ° W., 34 lks. dist., mkd. $\frac{1}{4}$ S 2 BT.


40.50 Stream 8 lks. wide, 12 ins. deep, course S. 70° E. from N. 60° W.

43.10 Leave bottom and timber, bearing N. 60° W. and S. 70° E.; asc. 95 ft. on S. slope.

46.90 Slope changes to SW.; asc. 85 ft.

53.97 Intersect the 9th Standard Parallel North.

Set an iron post, 3 ft. long, 2 ins. diam., in a mound of stone, with a rock 8x4x2 ins. mkd. with a cross (X) at base of post, for the closing cor. of secs. 1 and 2, with brass cap mkd.



From point of intersection the ^{standard} cor. of secs. 35 and 36, T. 46 N., R. 60 E., bears E., 17.80 chs. dist.

Land, broken benchland.
Soil, sandy loam surface, rock below.
Undergrowth, sagebrush, blackbrush, willows, yellow top and bunch grass.
Timber, aspen.
Grazing, poor to fair.

From the cor. of secs. 25, 26, 35, and 36.
West, on a temporary sectional correction line.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.00 Set temp. sec. cor. for secs. 26, 27, 34, and 35.

Thence

S. 0°01' W., on a random line, bet. secs. 34 and 35.

40.00 Set. temp. $\frac{1}{4}$ sec. cor.

81.14 Intersect S. bdy. of Tp. 4 lks. N. 87°49' W. of the cor. of secs. 34 and 35 only, which is an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in this book.

Thence

N. 0°01' E., on a true line, bet. secs. 34 and 35.

Desc. 100 ft. on a broken N. slope.

16.90 Enter creek bottom, bearing E. and W.; across nearly level bottom.

19.50 Road, bears E. and W.; asc. 15 ft.