


Subdivision of T. 45 N., R. 60 E.

Chains  
40.00

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.



raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

Asc. 205 ft. on a broken NE. slope.

68.80

Point of spur, projecting from S.; desc. 15 ft.

71.30

Draw, course NE.; asc. 110 ft. on a steep SE. slope.

80.00

The cor. of secs. 2, 3, 10; and 11.

Land, rolling benchland.

Soil, sandy loam; 3rd rate.

Undergrowth, sagebrush, blackbrush, yellow top. Bunch grass.

No timber.

Grazing, fair.

N.  $0^{\circ}01'$  E., bet. secs. 2 and 3.

Over rolling foothills; desc. 90 ft. on a NE. slope.

7.20

Draw, course N.  $70^{\circ}$  E. from head 5 chs. S.  $70^{\circ}$  W.; asc. 45 ft. on a SE. slope.

12.00

Point of spur, projecting from W.; desc. 15 ft. on NE. slope.

20.00

Divide, bears S.  $70^{\circ}$  W. and E.; desc. 105 ft. on NW. slope.

26.00


Stream, 2 lks. wide, 1 in. deep, course N.  $70^{\circ}$  E. from S.  $80^{\circ}$  W.; asc. 95 ft. on a S. slope.

31.00

Spur, projects S.  $30^{\circ}$  E.; asc. 21 ft. on S. slope.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to solid rock, in a mound of stone, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.



from which

A mahogany 6 ins. diam., bears S.  $64^{\circ}$  E., 63 lks. dist., mkd.  $\frac{1}{4}$  S2BT.

A mahogany 8 ins. diam., bears S.  $31\frac{1}{2}^{\circ}$  W., 63 lks. dist., mkd.  $\frac{1}{4}$  S3 BT.

41.60

Spur, projects E. from N.  $80^{\circ}$  W.; desc. 10 ft.

43.30

Draw, course N.  $70^{\circ}$  E. from N.  $80^{\circ}$  W.; asc. 95 ft. on a S. slope.

54.01

On spur, projecting E.

Intersect the Ninth Standard Parallel North.

Set an iron post, 3 ft. long, 2 ins. diam., 13 ins. in