


Subdivision of T. 45 N., R. 60 E.

Chains



Cross (X) mkd. on solid rock at base of post.

Continue over mountainous country.

40.00


Cross (X) mkd. on S. face of ledge at true $\frac{1}{4}$ sec. cor. point.

Asc. 355. ft. on a rocky broken SW. slope.

54.14

Intersect the Ninth Standard Parallel North.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for the closing cor. of secs. 4 and 5, with brass cap mkd.



from which

A mahogany, 6 ins. diam., bears S. $29\frac{1}{2}^\circ$ W., 82 lks. dist., mkd. T45N R60E S5 CC BT.

Raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high S. of cor.

From point of intersection the ^{standard} cor. of secs. 32 and 33 T. 46 N., R. 60 E., which is an iron post 2 ins. diam., firmly set, mkd. and witnessed as described in this book, bears East 17.64 chs. dist.

Land, mountainous.
Soil, sandy loam surface 6 ins. deep, rock below; 3rd rate.
Undergrowth, sagebrush, buckbrush, yellow top and manzanita. Bunch grass.
Timber, aspen and mahogany.
Grazing, fair.

From the cor. of secs. 28, 29, 32, and 33.

West, on a temporary sectional correction line.

40.00

Set temp. $\frac{1}{4}$ sec. cor.

80.00

Set temp. cor. for secs. 29, 30, 31, and 32.

Thence

S. $0^\circ 01'$ E., on a random line, bet. secs. 31 and 32.

40.00

Set temp. $\frac{1}{4}$ sec. cor.

82.05

Intersect S. bdy. of Tp. 6 lks. N $88^\circ 09'$ E. of the cor. of secs. 31 and 32 only, which is an iron post 2 ins. diam., firmly set, mkd. and witnessed as described in this book.

Thence