

Subdivision of T. 45 N., R. 60 E.

Chains
40.12

Set an iron post 3 ft. long, 1 in. diam., 15 ins. in the ground to solid rock, in a mound of stone, for witness $\frac{1}{4}$ sec. cor., with brass cap mkd.

S19

— W

S30C

1933

Cross (X) mkd. on solid rock at base of post.

Continue over mountainous country.

40.90

Point of spur, projecting from NE.; desc. 110 ft. on a SW. slope.

48.70

Draw, course S. 30° W. circling from NW.; asc. 25 ft. on a slight SE. slope.

59.90

Stream 12 lks. wide, 1 ft. deep, course SE. about 2 chs. then E., thick growth of aspen and cottonwood on each side of stream for about 1 ch. dist.; asc. 100 ft. on a NE. slope.

68.30

Point of spur, projecting from SW.; desc. 10 ft.

72.00

Stream 5 lks. wide 3 ins. deep, course N. 70° E., from SW., thick growth of willow, aspen, cottonwood, and mahogany along stream; asc. 110 ft. on a SE. slope.

80.00

Set an iron post 3 ft. long, 1 in. diam., 15 ins. in the ground to solid rock, in a mound of stone, for the cor. of lots 7 and 8 sec. 19, and lots 1 and 2 sec. 30, with brass cap mkd.

S19

7|8

— 2|1

S30

1933

Continue line; asc. 40 ft. on a SE. slope.

80.80

Point of spur, projecting from N. 20° W.; desc. 50 ft. on a SW. slope.

83.60

Draw, course SE. from N. 30° W.; asc. 120 ft. on a SE. slope.

88.65

On spur, projects SE. about 5 chs.

Intersect the E. bdy. of T. 45 N., R. 59 E., at a point from which the cor. of secs. 24 and 25, T. 45 N., R. 59 E., which is an iron post 2 ins. diam., firmly set, mkd. and witnessed as described in this book, bears S. 3 chs. dist.

Set an iron post 3 ft. long, 2 ins. diam., 6 ins. in the ground to solid rock, in a mound of stone, for the closing cor. of secs. 19 and 30, with brass cap mkd.

T45N

R59E R60E

S19 C

S24

S30 C

1933

from which

A mahogany 8 ins. diam., bears N. 28° E., 87 lks.