

494

Subdivision of T. 45 N., R. 60 E.

Chains 24.60	Spur, projects S. 20° W. from N.; desc. 590 ft. on a rocky W. slope along the N. side of a draw, course W.
40.00	Set an iron post 3 ft. long, 1 in. diam., 4 ins. in the ground to solid rock, in a mound of stone, for $\frac{1}{4}$ sec. cor., with brass cap mkd. S18 $\frac{1}{4}$ ——— S19 1933
	from which A mahogany 10 ins. diam., bears N. 31 $\frac{1}{2}$ ° E., 26 lks. dist., mkd. $\frac{1}{4}$ S18 BT. A mahogany 14 ins. diam., bears S. 42 $\frac{1}{2}$ ° W., 19 lks. dist., mkd. $\frac{1}{4}$ S19 BT. Cross (X) mkd. on solid rock at base of post. Continue over mountainous country; desc. 140 ft. on a W. slope.
43.40	Stream 3 lks. wide, 2 ins. deep, course S. 20° W.; asc. 120 ft. on a broken SE. slope.
50.50	Spur, projects S.; desc. 90 ft. on a SW. slope.
55.40	Stream 4 lks. wide, 3 ins. deep, course S. 20° E.; asc. 660 ft. on a broken E. slope.
70.60	Rim of mesa, bears N. 5 chs. and S. 10° E. 12 chs. then NW.; small spring bears N. 5° E. 9 chs. dist., a large spring bears N. 8 $\frac{1}{2}$ ° E. 30 chs. dist.; across top of mesa.
79.82	Set an iron post 3 ft. long, 1 in. diam., over a cross (X) on solid rock, in a mound of stone, for the witness cor. of lots 7 and 8, sec. 18, and lots 1 and 2, sec. 19, with brass cap mkd. S18 W 7   8 C 2   1 S19 1933
80.00	True point for lot cor. falls on sloping face of rock. Continue line.
81.20	Rim of mesa, bears NW. and SE.; desc. 285 ft. on a precipitous SW. slope.
88.77	Intersect the E. bdy. of T. 45 N., R. 59 E., at a point from which the cor. of secs. 13 and 24, T. 45 N., R. 59 E., which is an iron post 2 ins. diam., firmly set, mkd. and witnessed as described in this book, bears S., 2.79 chs. dist. Set an iron post 3 ft. long, 2 ins. diam., 22 ins. in the ground to solid rock, in a mound of stone, for the closing cor. of secs. 18 and 19, with brass cap mkd. T45N R59E R60E S18 C S13 S19 C 1933