

Dependent Resurvey of the West Bdy. of T. 46 N., R. 61 E.

Chains 50.75	Draw, course S. 30° W. from the NE.; asc. 150 ft. on a gentle S. slope.														
76.88	At point 80.00 chs. northing of the cor. of secs. 12 and 13 only, Set an iron post 3 ft. long, 2 ins. diam., 27 ins. in the ground, for the cor. of secs. 1 and 12 only, with brass cap mkd.														
	<table style="margin: auto;"> <tr><td colspan="2">T46N</td></tr> <tr><td>R60E</td><td>R61E</td></tr> <tr><td>S1</td><td> </td></tr> <tr><td colspan="2" style="border-top: 1px solid black;">S7</td></tr> <tr><td>S12</td><td> </td></tr> <tr><td colspan="2" style="border-top: 1px solid black;">1933</td></tr> </table>	T46N		R60E	R61E	S1		S7		S12		1933			
T46N															
R60E	R61E														
S1															
S7															
S12															
1933															
	raise a mound of stone 2 ft. base, 1½ ft. high, W. of cor.														
	Asc. 25 ft. on a S. slope.														
80.59	The cor. of secs. 1, 6, 7, and 12, which is a basalt stone 12x12x4 ins. mkd. with 5 grooves on the S. side. At cor. point, Set an iron post 3 ft. long, 2 ins. diam., 27 ins. in the ground, with the original monument alongside, for the cor. of secs. 6 and 7 only, with brass cap mkd.														
	<table style="margin: auto;"> <tr><td colspan="2">T46N</td></tr> <tr><td>R60E</td><td>R61E</td></tr> <tr><td>S1</td><td> </td></tr> <tr><td colspan="2" style="border-top: 1px solid black;">S6</td></tr> <tr><td>S1</td><td> </td></tr> <tr><td colspan="2" style="border-top: 1px solid black;">S7</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;">1933</td></tr> </table>	T46N		R60E	R61E	S1		S6		S1		S7		1933	
T46N															
R60E	R61E														
S1															
S6															
S1															
S7															
1933															
	raise a mound of stone 2 ft. base, 1½ ft. high, E. of cor.														
	Land, rolling benchland. Soil, shallow sandy loam surface, 3rd rate. Undergrowth, sagebrush, yellow top, and manzanita. Bunch grass. No timber. Grazing, fair.														
	N. 0°04' E., along the W. bdy. of sec. 6.														
	Over rolling hills; asc. 15 ft. on a S. slope.														
1.80	Divide, bears NE. and SW.; across top.														
15.80	Leave top bearing E. and W.; desc. 30 ft. on a broken N. slope.														
18.40	Road, bears N. 80° E. and S. 80° W.; desc. 180 ft. on a N. slope.														
32.00	Enter heavy aspen and balsam timber bearing E. and W.; desc. 105 ft. on a N. slope.														
36.29	At point 40.00 chs. northing of the cor. of secs. 1 and 12 only, Set an iron post 3 ft. long, 1 in. diam., 27 ins. in the ground, for the ½ sec. cor. of sec. 1 only, with brass cap mkd.														